

SikaLevel®-1100 RO

DECLARATION OF PERFORMANCE

No. 37566062

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	37566062
2	INTENDED USE/S	Screed material and floor screeds - corresponding to the basic performance requirements of EN 13813:2002: CA-C20-F6.
3	MANUFACTURER:	Sika Romania SRL Str. Izvor 92-96 Cladirea Forum III Bucuresti Sect. 5 www.sika.ro
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 4
6a	HARMONISED STANDARD:	EN 13813:2002
	Notified body/ies:	-

Declaration of Performance

SikaLevel®-1100 RO

37566062

24.09.2026 , ver. 1

1641

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire:	A1 _{fl}	System 4	EN 13813:2002
Release of corrosive substances:	CA	System 4	
Water permeability:	NPD	System 4	
Water vapour permeability:	NPD	System 4	
Compressive strength	C20	System 4	
Flexural strength	F6	System 4	
Wear resistance	NPD	System 4	
Sound insulation:	NPD	System 4	
Sound absorption:	NPD	System 4	
Thermal resistance:	NPD	System 4	
Chemical resistance:	NPD	System 4	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: George Bocai
Function: Head of R&D+QC
At Bucharest on 24.09.2026

Name: Cristian Kovacs
Function: Market Field Manager Flooring
At Bucharest on 24.09.2026

George Bocai

Kovacs Cristian

End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

SikaLevel®-1100 RO
37566062
24.09.2026 , ver. 1
1641



26

EN 13813:2002

37566062

Sika Romania SRL

Screed material and floor screeds - corresponding to the basic performance requirements of EN 13813:2002: CA-C20-F6.

Reaction to fire:	A1 _{fl}
-------------------	------------------

Release of corrosive substances:	CA
----------------------------------	----

Compressive strength	C20
----------------------	-----

Flexural strength	F6
-------------------	----

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

SikaLevel®-1100 RO

37566062

24.09.2026 , ver. 1

1641